



HeatWave

Underlay

A super soft
PU foam
underlay
which
is **flame
retardant**

■ Fire safety comes first

HeatWave is designed to be safer if a fire breaks out in the home, thanks to its flame retardant properties...so there's no need to worry about hidden dangers under your floor if the worst should happen.

■ That soft feeling...

HeatWave is made from very pure polyurethane foam, so is very soft and gives unbeatable underfoot comfort...sitting on your carpet will feel like sitting on your sofa!

■ Heatwave under the floor

HeatWave has a tog value of only 1.2, which allows underfloor heating to work away at keeping the room nice and warm.

Technical Data

Properties	Unit	Value Test	Method
Thickness	mm	8mm ± 10%	
Roll Weight	kg	13.3kg ± 10%	
Density	kg/m ³	110kg/m ³ ± 5%	
Classification		L/U Luxury Use	BS5808: 1991 (2011)
Thermal resistance	m ² K/W	0.12	EN 12664:2001
	tog	1.2	
Flammability (Hot Metal Nut Test)		Pass - Low Radius of effect	BS 4790:1987 (2009)
Flammability (reaction to fire classification)		Bfl-s1	GB 8624-2006 GB/T 11785-2005 GB/T 8626-2007
Impact Sound Reduction	dB	36	BS EN ISO 717-2:2013 BS EN ISO 10140-3:2010 (Estimated based on a similar product)
Guarantee		Lifetime of carpet	

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive

Liverpool L24 8RL

Tel: 0151 495 3434

Fax: 0151 427 0484

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Heavy
Traffic

Carpet



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Level
Floors

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use*

*Suitable for hotels and public buildings

Available in

Code QAU-HWA-01

Size 1.37m x 11m (15.07m²)

Thickness 8mm