100% recyclable PE foam wood underlay offering terrific value

■ Longer-lasting flooring

UniBase Bronze gives your floor covering the perfect level of support, to protect it from excess wear and even high impact damage - all of which helps your floor look good for longer!

Lightening the load

The ultra lightweight polyethylene foam material makes UniBase Bronze so easy to lift and manoeuvre...you won't believe just how much time and effort that can save you on every installation.

Faster fitting

Linit

There's no wasting time with UniBase Bronze - it's not only a lightweight to lift and move around, but really easy to cut and install so you can get on with the job.

Value

Mothod

Properties	
Density	

Technical Data

Froperties	OIIIL	value	Method
Density	kg/m³	20 <u>+</u> 2.0	internal
Impact Sound Reduction	dB	<u>~</u> 19 (2mm)	BSEN ISO-140-8
Temperature Stability (unloaded)	°C	75	internal
Thermal Conductivity of PE Foam measured at 10°C	W/m k	0.045	DIN 4108
Thermal Resistance of PE Foam	$\mathrm{m}^2\mathrm{k/W}$	0.044 (2mm)	DIN 4108
		0.067 (3mm)	DIN 4108
Maximum Compression Load	kN/m²	≤ 2.0	DIN EN 1606
Resistance to Compression at 25% deformation	to/m²	<u>~</u> 2.0	DIN 53 577
Tensile Strength, lengthwise*	N/mm²	≥ 0.30	DIN 53 571
Tensile Strength, crosswise*	N/mm²	≥ 0.15	DIN 53 571
Elongation at break, lengthwise*	%	<u>~</u> 100	DIN 53 571
Elongation at break, crosswise*	%	<u>~</u> 80	DIN 53 571

QA Flooring Solutions Ltd

Block H. Pickerings Road. Widnes, Cheshire WA8 8XW

Tel: 0151 495 3434 Fax: 0151 420 9062

Email: sales@qaflooringsolutions.com www.gaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Wood





Best for

Cushionina

Moisture

Sound Reduction

Floors

Underfloor Heating

Hard Wearing Heat

Use*

*Suitable for hotels and public buildings

Available in

Code	QAU-UBB-01
Size	1m x 10m (10m ²)
Thickness	2mm
Code	QAU-UBB-02
Size	1m x 15m (15m ²)
Thickness	2mm
Code	QAU-UBB-03
Size	1m x 15m (15m ²)
Thickness	3mm
Code	QAU-UBB-04
Size	1m x 25m (25m ²)
Thickness	2mm
Code	QAU-UBB-05
Size	1m x 120m (120m ²)
Thickness	2mm